



Message Implementation Guideline

orderResponseMessage

Model: OrderResponse
Version: 3.1.1
Variant: Switzerland Ideal Message Healthcare
Issue date: 04.09.2016
Author: rw

Angabe der Änderungen in 3.1.1

Version	Datum	Ersteller	Zusammenfassung der Änderungen
3.1	18.09.2015	Roland Weibel	Bearbeitung durch die Fachgruppe BiG – Beschaffung im Gesundheitswesen
3.1.1	22.08.2016	Roland Weibel	Anpassung an globale Usanzen und Verwendung von Batch anstelle von Lot für die Angabe einer Lot-/Batch-Nummer

Widerruf (Disclaimer)

Trotz aller Bemühungen, die Korrektheit der im vorliegenden Dokument enthaltenen GS1 System Standards sicherzustellen, erklären GS1 und jede weitere Partei, die an der Erstellung dieses Dokumentes beteiligt war, dass das vorliegende Dokument ohne ausdrückliche oder implizite Gewähr für Schäden oder Verluste, die in Zusammenhang mit der Verwendung dieses Dokumentes stehen, bereit gestellt wird. Das Dokument wird von Zeit zu Zeit auf Grund von Entwicklungen in der Technologie, Änderungen in den Standards oder neuen rechtlichen Gegebenheiten verändert.

Einige Produkte und Firmennamen, die hier erwähnt werden, können eingetragene Warenzeichen und/oder eingetragene Warenzeichen ihrer jeweiligen Firmen sein.

Structure

Occurrence	Element/Attribute
	orderResponse
1 .. 1	xsd:sequence
1 .. 1	creationDateTime
1 .. 1	documentStatusCode
1 .. 1	xsd:sequence
1 .. 1	orderResponseIdentification
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
0 .. 1	contentOwner
1 .. 1	xsd:sequence
1 .. 1	gln
1 .. 1	responseStatusCode
	<i>codeListVersion</i>
0 .. unbounded	orderResponseReasonCode
	<i>codeListVersion</i>
1 .. 1	buyer
1 .. 1	xsd:sequence
0 .. 1	gln
1 .. 1	seller
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. 1	billTo
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. 1	shipTo
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. 1	amendedDateTimeValue
1 .. 1	xsd:sequence
0 .. 1	requestedDeliveryDateRange
1 .. 1	xsd:sequence
0 .. 1	beginDate
0 .. 1	beginTime
0 .. 1	endDate
0 .. 1	endTime
1 .. 1	originalOrder
1 .. 1	xsd:sequence
1 .. 1	entityIdentification
1 .. 1	xsd:sequence
0 .. 1	creationDateTime
0 .. 1	revisionNumber
0 .. 1	lineltemNumber
0 .. 1	deliveryTerms
1 .. 1	xsd:sequence
0 .. 1	deliveryTermsLocation
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. unbounded	orderResponseLinitem
1 .. 1	xsd:sequence
1 .. 1	lineltemNumber
1 .. 1	confirmedQuantity
	<i>measurementUnitCode</i>

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	<i>codeListVersion</i>
0 .. unbounded	originalOrderLineItemNumber
0 .. unbounded	orderResponseReasonCode
0 .. 1	<i>codeListVersion</i>
0 .. 1	netPrice
required	<i>currencyCode</i>
	<i>codeListVersion</i>
1 .. 1	transactionalTradeItem
1 .. 1	xsd:sequence
1 .. 1	gtin
0 .. unbounded	additionalTradeItemIdentification
required	<i>additionalTradeItemIdentificationTypeCode</i>
	<i>codeListVersion</i>
1 .. 1	xsd:sequence
0 .. 1	tradeItemDescription
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. unbounded	transactionalItemData
1 .. 1	xsd:sequence
0 .. 1	batchNumber
0 .. 1	itemExpirationDate
0 .. unbounded	serialNumber
0 .. unbounded	serialNumberRange
1 .. 1	xsd:sequence
0 .. 1	maximumValue
0 .. 1	minimumValue
0 .. unbounded	colour
1 .. 1	xsd:sequence
0 .. 1	colourCode
required	<i>colourCodeListCode</i>
	<i>colourCodeListVersion</i>
0 .. unbounded	colourDescription
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. unbounded	size
1 .. 1	xsd:sequence
0 .. 1	descriptiveSize
required	<i>languageCode</i>
	<i>codeListVersion</i>
0 .. 1	sizeCode
required	<i>sizeCodeListCode</i>
	<i>sizeCodeListDescription</i>
	<i>codeListVersion</i>
	<i>sizeCodeListVersion</i>
0 .. 1	backOrderInformation
1 .. 1	xsd:sequence
1 .. 1	confirmedQuantity
1 .. 1	orderLogisticalInformation
1 .. 1	xsd:sequence
0 .. 1	inventoryLocation
1 .. 1	xsd:sequence
0 .. 1	gln
0 .. 1	ultimateConsignee
1 .. 1	xsd:sequence
0 .. 1	gln

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
0 .. 1	orderLogisticalDateInformation
1 .. 1	xsd:sequence
0 .. 1	requestedDeliveryDateRange
1 .. 1	xsd:sequence
0 .. 1	beginDate
0 .. 1	beginTime
0 .. 1	endDate
0 .. 1	endTime
0 .. 1	requestedDeliveryDateTime
1 .. 1	xsd:sequence
1 .. 1	date
0 .. 1	time
0 .. unbounded	orderResponseLineItemDetail
1 .. 1	xsd:sequence
1 .. 1	confirmedQuantity
1 .. 1	orderLogisticalInformation
1 .. 1	xsd:sequence
0 .. 1	orderLogisticalDateInformation
1 .. 1	xsd:sequence
0 .. 1	requestedDeliveryDateRange
1 .. 1	xsd:sequence
0 .. 1	beginDate
0 .. 1	beginTime
0 .. 1	endDate
0 .. 1	endTime
0 .. 1	requestedDeliveryDateTime
1 .. 1	xsd:sequence
1 .. 1	date
0 .. 1	time

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Guideline

Element/Attribute	Annotation																
orderResponse	Occurrence 1 .. 10000 Type order_response:OrderResponseType																
xsd:sequence creationDateTime	Occurrence 1 .. 1 Occurrence 1 .. 1 Type xsd:dateTime																
<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>creationDateTime</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Date and time when the document was created.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Erestellungsdatum und Zeit</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:Document.creationDateTime</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2012-06-15T11:00:00.000</td> </tr> </tbody> </table>		Fachgruppe BiG		Name FG BiG	creationDateTime	Status	1..1	Beschr. EDI	Date and time when the document was created.	Beschr. FG BiG	Erestellungsdatum und Zeit	GDD URI	urn:gs1:gdd:bie:Document.creationDateTime	Codeliste	-	Beispiel	2012-06-15T11:00:00.000
Fachgruppe BiG																	
Name FG BiG	creationDateTime																
Status	1..1																
Beschr. EDI	Date and time when the document was created.																
Beschr. FG BiG	Erestellungsdatum und Zeit																
GDD URI	urn:gs1:gdd:bie:Document.creationDateTime																
Codeliste	-																
Beispiel	2012-06-15T11:00:00.000																
documentStatusCode	Occurrence 1 .. 1 Type shared_common:DocumentStatusEnumerationType																
<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>documentStatusCode</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Indicates if the document is a copy or an original.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Dokument Status Code</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:Document.documentStatusCode</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>ORIGINAL</td> </tr> </tbody> </table>		Fachgruppe BiG		Name FG BiG	documentStatusCode	Status	1..1	Beschr. EDI	Indicates if the document is a copy or an original.	Beschr. FG BiG	Dokument Status Code	GDD URI	urn:gs1:gdd:bie:Document.documentStatusCode	Codeliste	-	Beispiel	ORIGINAL
Fachgruppe BiG																	
Name FG BiG	documentStatusCode																
Status	1..1																
Beschr. EDI	Indicates if the document is a copy or an original.																
Beschr. FG BiG	Dokument Status Code																
GDD URI	urn:gs1:gdd:bie:Document.documentStatusCode																
Codeliste	-																
Beispiel	ORIGINAL																
xsd:sequence orderResponseIdentification	Occurrence 1 .. 1 Occurrence 1 .. 1 Type shared_common:EntityIdentificationType																
xsd:sequence entityIdentification	Occurrence 1 .. 1 Occurrence 1 .. 1 Type restriction (xsd:string) Length 1 .. 80																
<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>entityIdentification</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The unique identifier of the piece of information, such as the object identifier or the document identifier</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Bestellnummer aus ERP Buyer</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:EntityIdentification</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>4500000065487</td> </tr> </tbody> </table>		Fachgruppe BiG		Name FG BiG	entityIdentification	Status	0..1	Beschr. EDI	The unique identifier of the piece of information, such as the object identifier or the document identifier	Beschr. FG BiG	Bestellnummer aus ERP Buyer	GDD URI	urn:gs1:gdd:bie:EntityIdentification	Codeliste	-	Beispiel	4500000065487
Fachgruppe BiG																	
Name FG BiG	entityIdentification																
Status	0..1																
Beschr. EDI	The unique identifier of the piece of information, such as the object identifier or the document identifier																
Beschr. FG BiG	Bestellnummer aus ERP Buyer																
GDD URI	urn:gs1:gdd:bie:EntityIdentification																
Codeliste	-																
Beispiel	4500000065487																
contentOwner	Occurrence 0 .. 1 Type shared_common:PartyIdentificationType																
xsd:sequence gln	Occurrence 1 .. 1 Occurrence 1 .. 1 Type shared_common:GLNType Pattern \d{13}																
<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>GLN</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used</td> </tr> </tbody> </table>		Fachgruppe BiG		Name FG BiG	GLN	Status	1..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used								
Fachgruppe BiG																	
Name FG BiG	GLN																
Status	1..1																
Beschr. EDI	Global Location Number (GLN), the GS1 key used																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
-------------------	------------

	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td></td> <td>for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Besteller</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification_gln</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> </tbody> </table>	Fachgruppe BiG			for the identification of parties and locations.	Beschr. FG BiG	GLN des Besteller	GDD URI	urn:gs1:gdd:bie:PartyIdentification_gln	Codeliste	-	Beispiel	7612345670010				
Fachgruppe BiG																	
	for the identification of parties and locations.																
Beschr. FG BiG	GLN des Besteller																
GDD URI	urn:gs1:gdd:bie:PartyIdentification_gln																
Codeliste	-																
Beispiel	7612345670010																
responseStatusCode	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:ResponseStatusCodeType</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	ecom_common:ResponseStatusCodeType	Length	1 .. 80										
Occurrence	1 .. 1																
Type	ecom_common:ResponseStatusCodeType																
Length	1 .. 80																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>responseStatusCode</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying the type of response. Example: Accepted.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Code, der den Antworttyp spezifiziert.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponse.responseStatusCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:ResponseStatusCode</td> </tr> <tr> <td>Beispiel</td> <td>Accepted</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	responseStatusCode	Status	1..1	Beschr. EDI	Code specifying the type of response. Example: Accepted.	Beschr. FG BiG	Code, der den Antworttyp spezifiziert.	GDD URI	urn:gs1:gdd:bie:OrderResponse.responseStatusCode	Codeliste	urn:gs1:gdd:cl:ResponseStatusCode	Beispiel	Accepted
Fachgruppe BiG																	
Name FG BiG	responseStatusCode																
Status	1..1																
Beschr. EDI	Code specifying the type of response. Example: Accepted.																
Beschr. FG BiG	Code, der den Antworttyp spezifiziert.																
GDD URI	urn:gs1:gdd:bie:OrderResponse.responseStatusCode																
Codeliste	urn:gs1:gdd:cl:ResponseStatusCode																
Beispiel	Accepted																
<i>codeListVersion</i>	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 35												
Type	restriction (xsd:string)																
Length	1 .. 35																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying a response status. Allowed code values are specified in GS1 Code List ResponseStatusCode.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Version der Codeliste; Aktuelle Version 1.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:cl:ResponseStatusCode</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>1</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	Code specifying a response status. Allowed code values are specified in GS1 Code List ResponseStatusCode.	Beschr. FG BiG	Version der Codeliste; Aktuelle Version 1.	GDD URI	urn:gs1:gdd:cl:ResponseStatusCode	Codeliste	-	Beispiel	1
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	Code specifying a response status. Allowed code values are specified in GS1 Code List ResponseStatusCode.																
Beschr. FG BiG	Version der Codeliste; Aktuelle Version 1.																
GDD URI	urn:gs1:gdd:cl:ResponseStatusCode																
Codeliste	-																
Beispiel	1																
orderResponseReasonCode	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. unbounded</td> </tr> <tr> <td>Type</td> <td>ecom_common:ErrorOrWarningCodeType</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> </tbody> </table>	Occurrence	0 .. unbounded	Type	ecom_common:ErrorOrWarningCodeType	Length	1 .. 80										
Occurrence	0 .. unbounded																
Type	ecom_common:ErrorOrWarningCodeType																
Length	1 .. 80																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>orderResponseReasonCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Grund für die Modifikation oder Rückweisung; Werte aus der entsprechenden Code Liste.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bd:ErrorOrWarningCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:ErrorOrWarningCode</td> </tr> <tr> <td>Beispiel</td> <td>MISSING_DATA</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	orderResponseReasonCode	Status	0..1	Beschr. EDI	Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.	Beschr. FG BiG	Grund für die Modifikation oder Rückweisung; Werte aus der entsprechenden Code Liste.	GDD URI	urn:gs1:gdd:bd:ErrorOrWarningCode	Codeliste	urn:gs1:gdd:cl:ErrorOrWarningCode	Beispiel	MISSING_DATA
Fachgruppe BiG																	
Name FG BiG	orderResponseReasonCode																
Status	0..1																
Beschr. EDI	Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.																
Beschr. FG BiG	Grund für die Modifikation oder Rückweisung; Werte aus der entsprechenden Code Liste.																
GDD URI	urn:gs1:gdd:bd:ErrorOrWarningCode																
Codeliste	urn:gs1:gdd:cl:ErrorOrWarningCode																
Beispiel	MISSING_DATA																
<i>codeListVersion</i>	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 35												
Type	restriction (xsd:string)																
Length	1 .. 35																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying an error or warning. Allowed code</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	Code specifying an error or warning. Allowed code								
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	Code specifying an error or warning. Allowed code																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td></td> <td>values are specified in GS1 Code List ErrorOrWarningCode.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Version der Codeliste</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:cl:ErrorOrWarningCode</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2</td> </tr> </tbody> </table>	Fachgruppe BiG			values are specified in GS1 Code List ErrorOrWarningCode.	Beschr. FG BiG	Version der Codeliste	GDD URI	urn:gs1:gdd:cl:ErrorOrWarningCode	Codeliste	-	Beispiel	2				
Fachgruppe BiG																	
	values are specified in GS1 Code List ErrorOrWarningCode.																
Beschr. FG BiG	Version der Codeliste																
GDD URI	urn:gs1:gdd:cl:ErrorOrWarningCode																
Codeliste	-																
Beispiel	2																
buyer	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Käufers</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification.gln</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.	Beschr. FG BiG	GLN des Käufers	GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln	Beispiel	7612345670010		
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.																
Beschr. FG BiG	GLN des Käufers																
GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln																
Beispiel	7612345670010																
xsd:sequence gln	<table border="1"> <tbody> <tr> <td>Occurence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:GLNType</td> </tr> <tr> <td>Pattern</td> <td>\d{13}</td> </tr> </tbody> </table>	Occurence	1 .. 1	Type	shared_common:GLNType	Pattern	\d{13}										
Occurence	1 .. 1																
Type	shared_common:GLNType																
Pattern	\d{13}																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Identifies the party to which products or services are sold.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Käufers.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponse.buyer.TransactionParty</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345000121</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Identifies the party to which products or services are sold.	Beschr. FG BiG	GLN des Käufers.	GDD URI	urn:gs1:gdd:bie:OrderResponse.buyer.TransactionParty	Codeliste	-	Beispiel	7612345000121
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Identifies the party to which products or services are sold.																
Beschr. FG BiG	GLN des Käufers.																
GDD URI	urn:gs1:gdd:bie:OrderResponse.buyer.TransactionParty																
Codeliste	-																
Beispiel	7612345000121																
seller	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Identifies the party which sells products or services to a buyer.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Verkäufers.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponse.seller.TransactionParty</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345000121</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Identifies the party which sells products or services to a buyer.	Beschr. FG BiG	GLN des Verkäufers.	GDD URI	urn:gs1:gdd:bie:OrderResponse.seller.TransactionParty	Codeliste	-	Beispiel	7612345000121
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Identifies the party which sells products or services to a buyer.																
Beschr. FG BiG	GLN des Verkäufers.																
GDD URI	urn:gs1:gdd:bie:OrderResponse.seller.TransactionParty																
Codeliste	-																
Beispiel	7612345000121																
xsd:sequence gln	<table border="1"> <tbody> <tr> <td>Occurence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:GLNType</td> </tr> <tr> <td>Pattern</td> <td>\d{13}</td> </tr> </tbody> </table>	Occurence	1 .. 1	Type	shared_common:GLNType	Pattern	\d{13}										
Occurence	1 .. 1																
Type	shared_common:GLNType																
Pattern	\d{13}																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Identifies the party which sells products or services to a buyer.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Verkäufers.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponse.seller.TransactionParty</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345000121</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Identifies the party which sells products or services to a buyer.	Beschr. FG BiG	GLN des Verkäufers.	GDD URI	urn:gs1:gdd:bie:OrderResponse.seller.TransactionParty	Codeliste	-	Beispiel	7612345000121
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Identifies the party which sells products or services to a buyer.																
Beschr. FG BiG	GLN des Verkäufers.																
GDD URI	urn:gs1:gdd:bie:OrderResponse.seller.TransactionParty																
Codeliste	-																
Beispiel	7612345000121																
billTo	<table border="1"> <tbody> <tr> <td>Occurence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:TransactionalPartyType</td> </tr> <tr> <td>Occurence</td> <td>1 .. 1</td> </tr> </tbody> </table>	Occurence	0 .. 1	Type	ecom_common:TransactionalPartyType	Occurence	1 .. 1										
Occurence	0 .. 1																
Type	ecom_common:TransactionalPartyType																
Occurence	1 .. 1																
xsd:sequence	<table border="1"> <tbody> <tr> <td>Occurence</td> <td>1 .. 1</td> </tr> </tbody> </table>	Occurence	1 .. 1														
Occurence	1 .. 1																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
gln	<p>Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13}</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Rechnungsempfängers</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification.gln</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.	Beschr. FG BiG	GLN des Rechnungsempfängers	GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln	Codeliste	-	Beispiel	7612345670010
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.																
Beschr. FG BiG	GLN des Rechnungsempfängers																
GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln																
Codeliste	-																
Beispiel	7612345670010																
shipTo	<p>Occurrence 0 .. 1 Type ecom_common:TransactionalPartyType</p>																
<i>xsd:sequence</i>	<p>Occurrence 1 .. 1</p>																
gln	<p>Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13}</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Empfängers</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification.gln</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.	Beschr. FG BiG	GLN des Empfängers	GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln	Codeliste	-	Beispiel	7612345670010
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.																
Beschr. FG BiG	GLN des Empfängers																
GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln																
Codeliste	-																
Beispiel	7612345670010																
amendedDateTimeValue	<p>Occurrence 0 .. 1 Type ecom_common:OrderLogisticalDateInformationType</p>																
<i>xsd:sequence</i>	<p>Occurrence 1 .. 1</p>																
requestedDeliveryDateRange	<p>Occurrence 0 .. 1 Type shared_common:DateTimeRangeType</p>																
<i>xsd:sequence</i>	<p>Occurrence 1 .. 1</p>																
beginDate	<p>Occurrence 0 .. 1 Type xsd:date</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>beginDate</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Date specifying the first day for the date time range.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeitfenster für Lieferung, Startdatum</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateTimeRange.beginDate</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2014-07-31</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	beginDate	Status	0..1	Beschr. EDI	Date specifying the first day for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Startdatum	GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginDate	Codeliste	-	Beispiel	2014-07-31
Fachgruppe BiG																	
Name FG BiG	beginDate																
Status	0..1																
Beschr. EDI	Date specifying the first day for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Startdatum																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginDate																
Codeliste	-																
Beispiel	2014-07-31																
beginTime	<p>Occurrence 0 .. 1 Type xsd:time</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>beginTime</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Time specifying the start time for the date time range.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeitfenster für Lieferung, Startzeit</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	beginTime	Status	0..1	Beschr. EDI	Time specifying the start time for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Startzeit						
Fachgruppe BiG																	
Name FG BiG	beginTime																
Status	0..1																
Beschr. EDI	Time specifying the start time for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Startzeit																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.beginTime</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>08:00</td></tr> </table>	Fachgruppe BiG		GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginTime	Codeliste	-	Beispiel	08:00								
Fachgruppe BiG																	
GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginTime																
Codeliste	-																
Beispiel	08:00																
endDate	<table border="1"> <tr><td>Occurrence</td><td>0 .. 1</td></tr> <tr><td>Type</td><td>xsd:date</td></tr> </table>	Occurrence	0 .. 1	Type	xsd:date												
Occurrence	0 .. 1																
Type	xsd:date																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>endDate</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Date specifying the last day for the date time range.</td></tr> <tr><td>Beschr. FG BiG</td><td>Zeitfenster für Lieferung, Enddatum</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.endDate</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>2014-08-05</td></tr> </table>	Fachgruppe BiG		Name FG BiG	endDate	Status	0..1	Beschr. EDI	Date specifying the last day for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Enddatum	GDD URI	urn:gs1:gdd:bie:DateTimeRange.endDate	Codeliste	-	Beispiel	2014-08-05
Fachgruppe BiG																	
Name FG BiG	endDate																
Status	0..1																
Beschr. EDI	Date specifying the last day for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Enddatum																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.endDate																
Codeliste	-																
Beispiel	2014-08-05																
endTime	<table border="1"> <tr><td>Occurrence</td><td>0 .. 1</td></tr> <tr><td>Type</td><td>xsd:time</td></tr> </table>	Occurrence	0 .. 1	Type	xsd:time												
Occurrence	0 .. 1																
Type	xsd:time																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>endTime</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Time specifying the end time for the date time range.</td></tr> <tr><td>Beschr. FG BiG</td><td>Zeitfenster für Lieferung, Endzeit</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.endTime</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>17:00</td></tr> </table>	Fachgruppe BiG		Name FG BiG	endTime	Status	0..1	Beschr. EDI	Time specifying the end time for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Endzeit	GDD URI	urn:gs1:gdd:bie:DateTimeRange.endTime	Codeliste	-	Beispiel	17:00
Fachgruppe BiG																	
Name FG BiG	endTime																
Status	0..1																
Beschr. EDI	Time specifying the end time for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Endzeit																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.endTime																
Codeliste	-																
Beispiel	17:00																
originalOrder	<table border="1"> <tr><td>Occurrence</td><td>1 .. 1</td></tr> <tr><td>Type</td><td>shared_common:DocumentReferenceType</td></tr> </table>	Occurrence	1 .. 1	Type	shared_common:DocumentReferenceType												
Occurrence	1 .. 1																
Type	shared_common:DocumentReferenceType																
xsd:sequence	<table border="1"> <tr><td>Occurrence</td><td>1 .. 1</td></tr> <tr><td>Type</td><td>restriction (xsd:string)</td></tr> <tr><td>Length</td><td>1 .. 80</td></tr> </table>	Occurrence	1 .. 1	Type	restriction (xsd:string)	Length	1 .. 80										
Occurrence	1 .. 1																
Type	restriction (xsd:string)																
Length	1 .. 80																
entityIdentification	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>entityIdentification</td></tr> <tr><td>Status</td><td>1..1</td></tr> <tr><td>Beschr. EDI</td><td>Information identifying a piece of information, such as an object or document.</td></tr> <tr><td>Beschr. FG BiG</td><td>Beschreibung Basisdokument</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:EntityIdentification</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>1520008999665</td></tr> </table>	Fachgruppe BiG		Name FG BiG	entityIdentification	Status	1..1	Beschr. EDI	Information identifying a piece of information, such as an object or document.	Beschr. FG BiG	Beschreibung Basisdokument	GDD URI	urn:gs1:gdd:bie:EntityIdentification	Codeliste	-	Beispiel	1520008999665
Fachgruppe BiG																	
Name FG BiG	entityIdentification																
Status	1..1																
Beschr. EDI	Information identifying a piece of information, such as an object or document.																
Beschr. FG BiG	Beschreibung Basisdokument																
GDD URI	urn:gs1:gdd:bie:EntityIdentification																
Codeliste	-																
Beispiel	1520008999665																
xsd:sequence	<table border="1"> <tr><td>Occurrence</td><td>1 .. 1</td></tr> <tr><td>Type</td><td>xsd:dateTime</td></tr> </table>	Occurrence	1 .. 1	Type	xsd:dateTime												
Occurrence	1 .. 1																
Type	xsd:dateTime																
creationDateTime	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>creationDateTime</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Date and time when the document was created.</td></tr> <tr><td>Beschr. FG BiG</td><td>Erestellungsdatum und Zeit der Bestellung</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:Document.creationDateTime</td></tr> <tr><td>Codeliste</td><td>-</td></tr> </table>	Fachgruppe BiG		Name FG BiG	creationDateTime	Status	0..1	Beschr. EDI	Date and time when the document was created.	Beschr. FG BiG	Erestellungsdatum und Zeit der Bestellung	GDD URI	urn:gs1:gdd:bie:Document.creationDateTime	Codeliste	-		
Fachgruppe BiG																	
Name FG BiG	creationDateTime																
Status	0..1																
Beschr. EDI	Date and time when the document was created.																
Beschr. FG BiG	Erestellungsdatum und Zeit der Bestellung																
GDD URI	urn:gs1:gdd:bie:Document.creationDateTime																
Codeliste	-																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																								
revisionNumber	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Beispiel</td> <td>2012-06-15T11:00:00.000</td> </tr> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>xsd:positiveInteger</td> </tr> <tr> <td>FractionDigits</td> <td>0</td> </tr> <tr> <td>Inclusive</td> <td>1 ..</td> </tr> </tbody> </table>	Fachgruppe BiG		Beispiel	2012-06-15T11:00:00.000	Occurrence	0 .. 1	Type	xsd:positiveInteger	FractionDigits	0	Inclusive	1 ..												
Fachgruppe BiG																									
Beispiel	2012-06-15T11:00:00.000																								
Occurrence	0 .. 1																								
Type	xsd:positiveInteger																								
FractionDigits	0																								
Inclusive	1 ..																								
lineltemNumber	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>revisionNumber</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Number to be used for identification and referencing of subsequent updates to a business document.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Dokumentenversion</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DocumentReference. revisionNumber</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>1.5</td> </tr> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>xsd:positiveInteger</td> </tr> <tr> <td>FractionDigits</td> <td>0</td> </tr> <tr> <td>Inclusive</td> <td>1 ..</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	revisionNumber	Status	0..1	Beschr. EDI	Number to be used for identification and referencing of subsequent updates to a business document.	Beschr. FG BiG	Dokumentenversion	GDD URI	urn:gs1:gdd:bie:DocumentReference. revisionNumber	Codeliste	-	Beispiel	1.5	Occurrence	0 .. 1	Type	xsd:positiveInteger	FractionDigits	0	Inclusive	1 ..
Fachgruppe BiG																									
Name FG BiG	revisionNumber																								
Status	0..1																								
Beschr. EDI	Number to be used for identification and referencing of subsequent updates to a business document.																								
Beschr. FG BiG	Dokumentenversion																								
GDD URI	urn:gs1:gdd:bie:DocumentReference. revisionNumber																								
Codeliste	-																								
Beispiel	1.5																								
Occurrence	0 .. 1																								
Type	xsd:positiveInteger																								
FractionDigits	0																								
Inclusive	1 ..																								
deliveryTerms	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>lineltemNumber</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Provides the line number associated to the Configure To Order Line Item.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeilennummer Basisdokument</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:ConfigureToOrderLineItem. lineltemNumber</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>3</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	lineltemNumber	Status	0..1	Beschr. EDI	Provides the line number associated to the Configure To Order Line Item.	Beschr. FG BiG	Zeilennummer Basisdokument	GDD URI	urn:gs1:gdd:bie:ConfigureToOrderLineItem. lineltemNumber	Codeliste	-	Beispiel	3								
Fachgruppe BiG																									
Name FG BiG	lineltemNumber																								
Status	0..1																								
Beschr. EDI	Provides the line number associated to the Configure To Order Line Item.																								
Beschr. FG BiG	Zeilennummer Basisdokument																								
GDD URI	urn:gs1:gdd:bie:ConfigureToOrderLineItem. lineltemNumber																								
Codeliste	-																								
Beispiel	3																								
<i>xsd:sequence</i>																									
deliveryTermsLocation	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:DeliveryTermsType</td> </tr> </tbody> </table>	Occurrence	0 .. 1	Type	ecom_common:DeliveryTermsType																				
Occurrence	0 .. 1																								
Type	ecom_common:DeliveryTermsType																								
<i>xsd:sequence</i>																									
gln	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:LogisticLocationType</td> </tr> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:GLNType</td> </tr> <tr> <td>Pattern</td> <td>\d{13}</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	ecom_common:LogisticLocationType	Occurrence	0 .. 1	Type	shared_common:GLNType	Pattern	\d{13}														
Occurrence	1 .. 1																								
Type	ecom_common:LogisticLocationType																								
Occurrence	0 .. 1																								
Type	shared_common:GLNType																								
Pattern	\d{13}																								
orderResponseLinItem	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Endempfängers</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification.gln</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> <tr> <td>Occurrence</td> <td>0 .. unbounded</td> </tr> <tr> <td>Type</td> <td>order_response:OrderResponseLinItemType</td> </tr> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.	Beschr. FG BiG	GLN des Endempfängers	GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln	Codeliste	-	Beispiel	7612345670010	Occurrence	0 .. unbounded	Type	order_response:OrderResponseLinItemType	Occurrence	1 .. 1		
Fachgruppe BiG																									
Name FG BiG	gln																								
Status	0..1																								
Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.																								
Beschr. FG BiG	GLN des Endempfängers																								
GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln																								
Codeliste	-																								
Beispiel	7612345670010																								
Occurrence	0 .. unbounded																								
Type	order_response:OrderResponseLinItemType																								
Occurrence	1 .. 1																								
<i>xsd:sequence</i>																									

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																
lineltemNumber	<p>Occurrence 1 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 ..</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>lineltemNumber</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Provides the line number associated to the Order Response Line Item.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Auftragsbestätigungszeile Nummer</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponseLineItem.lineltemNumber</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>1</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	lineltemNumber	Status	1..1	Beschr. EDI	Provides the line number associated to the Order Response Line Item.	Beschr. FG BiG	Auftragsbestätigungszeile Nummer	GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.lineltemNumber	Codeliste	-	Beispiel	1
Fachgruppe BiG																	
Name FG BiG	lineltemNumber																
Status	1..1																
Beschr. EDI	Provides the line number associated to the Order Response Line Item.																
Beschr. FG BiG	Auftragsbestätigungszeile Nummer																
GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.lineltemNumber																
Codeliste	-																
Beispiel	1																
confirmedQuantity	<p>Occurrence 1 .. 1 Type shared_common:QuantityType</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>confirmedQuantity</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The quantity which has been confirmed by the seller.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Bestätigte Menge</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity</td> </tr> <tr> <td>Beispiel</td> <td>10</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	confirmedQuantity	Status	1..1	Beschr. EDI	The quantity which has been confirmed by the seller.	Beschr. FG BiG	Bestätigte Menge	GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity	Beispiel	10		
Fachgruppe BiG																	
Name FG BiG	confirmedQuantity																
Status	1..1																
Beschr. EDI	The quantity which has been confirmed by the seller.																
Beschr. FG BiG	Bestätigte Menge																
GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity																
Beispiel	10																
measurementUnitCode	<p>Type restriction (xsd:string) Length 1 .. 80</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>measurementUnitCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>measurementUnitCode. Codeliste: http://www.unece.org/fileadmin/DAM/cefact/</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Mengeneinheiten</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:Quantity.measurementUnitCode</td> </tr> <tr> <td>Beispiel</td> <td>AP</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	measurementUnitCode	Status	0..1	Beschr. EDI	measurementUnitCode. Codeliste: http://www.unece.org/fileadmin/DAM/cefact/	Beschr. FG BiG	Mengeneinheiten	GDD URI	urn:gs1:gdd:bdt:Quantity.measurementUnitCode	Beispiel	AP		
Fachgruppe BiG																	
Name FG BiG	measurementUnitCode																
Status	0..1																
Beschr. EDI	measurementUnitCode. Codeliste: http://www.unece.org/fileadmin/DAM/cefact/																
Beschr. FG BiG	Mengeneinheiten																
GDD URI	urn:gs1:gdd:bdt:Quantity.measurementUnitCode																
Beispiel	AP																
codeListVersion	<p>Type restriction (xsd:string) Length 1 .. 35</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The snapshot of the code list at a certain point in time.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Version der Codeliste</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:Quantity.measurementUnitCode</td> </tr> <tr> <td>Beispiel</td> <td>21</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	The snapshot of the code list at a certain point in time.	Beschr. FG BiG	Version der Codeliste	GDD URI	urn:gs1:gdd:bdt:Quantity.measurementUnitCode	Beispiel	21		
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	The snapshot of the code list at a certain point in time.																
Beschr. FG BiG	Version der Codeliste																
GDD URI	urn:gs1:gdd:bdt:Quantity.measurementUnitCode																
Beispiel	21																
originalOrderLineItemNumber	<p>Occurrence 0 .. 1 Type xsd:positiveInteger FractionDigits 0 Inclusive 1 ..</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>originalOrderLineItemNumber</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	originalOrderLineItemNumber												
Fachgruppe BiG																	
Name FG BiG	originalOrderLineItemNumber																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>A reference to the original order line item number.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Referenz zur Bestellzeilennummer</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponseLineItem.originalOrderLineItemNumber</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>1</td> </tr> </tbody> </table>	Fachgruppe BiG		Status	0..1	Beschr. EDI	A reference to the original order line item number.	Beschr. FG BiG	Referenz zur Bestellzeilennummer	GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.originalOrderLineItemNumber	Codeliste	-	Beispiel	1		
Fachgruppe BiG																	
Status	0..1																
Beschr. EDI	A reference to the original order line item number.																
Beschr. FG BiG	Referenz zur Bestellzeilennummer																
GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.originalOrderLineItemNumber																
Codeliste	-																
Beispiel	1																
orderResponseReasonCode	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. unbounded</td> </tr> <tr> <td>Type</td> <td>ecom_common:ErrorOrWarningCodeType</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> </tbody> </table>	Occurrence	0 .. unbounded	Type	ecom_common:ErrorOrWarningCodeType	Length	1 .. 80										
Occurrence	0 .. unbounded																
Type	ecom_common:ErrorOrWarningCodeType																
Length	1 .. 80																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>orderResponseReasonCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Grund für die Modifikation oder Rückweisung; Werte aus der entsprechenden Code Liste.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:cl:ErrorOrWarningCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:ErrorOrWarningCode</td> </tr> <tr> <td>Beispiel</td> <td>MISSING_DATA</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	orderResponseReasonCode	Status	0..1	Beschr. EDI	Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.	Beschr. FG BiG	Grund für die Modifikation oder Rückweisung; Werte aus der entsprechenden Code Liste.	GDD URI	urn:gs1:gdd:cl:ErrorOrWarningCode	Codeliste	urn:gs1:gdd:cl:ErrorOrWarningCode	Beispiel	MISSING_DATA
Fachgruppe BiG																	
Name FG BiG	orderResponseReasonCode																
Status	0..1																
Beschr. EDI	Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.																
Beschr. FG BiG	Grund für die Modifikation oder Rückweisung; Werte aus der entsprechenden Code Liste.																
GDD URI	urn:gs1:gdd:cl:ErrorOrWarningCode																
Codeliste	urn:gs1:gdd:cl:ErrorOrWarningCode																
Beispiel	MISSING_DATA																
<i>codeListVersion</i>	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 35												
Type	restriction (xsd:string)																
Length	1 .. 35																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Version der Codeliste</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:cl:ErrorOrWarningCode</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.	Beschr. FG BiG	Version der Codeliste	GDD URI	urn:gs1:gdd:cl:ErrorOrWarningCode	Codeliste	-	Beispiel	2
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	Code specifying an error or warning. Allowed code values are specified in GS1 Code List ErrorOrWarningCode.																
Beschr. FG BiG	Version der Codeliste																
GDD URI	urn:gs1:gdd:cl:ErrorOrWarningCode																
Codeliste	-																
Beispiel	2																
netPrice	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:AmountType</td> </tr> </tbody> </table>	Occurrence	0 .. 1	Type	shared_common:AmountType												
Occurrence	0 .. 1																
Type	shared_common:AmountType																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>netPrice</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Identifies the net price of the item.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Nettopreis pro Artikel</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:ConfigureToOrderLineItem.netPrice</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>100.10</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	netPrice	Status	0..1	Beschr. EDI	Identifies the net price of the item.	Beschr. FG BiG	Nettopreis pro Artikel	GDD URI	urn:gs1:gdd:bie:ConfigureToOrderLineItem.netPrice	Codeliste	-	Beispiel	100.10
Fachgruppe BiG																	
Name FG BiG	netPrice																
Status	0..1																
Beschr. EDI	Identifies the net price of the item.																
Beschr. FG BiG	Nettopreis pro Artikel																
GDD URI	urn:gs1:gdd:bie:ConfigureToOrderLineItem.netPrice																
Codeliste	-																
Beispiel	100.10																
<i>currencyCode</i>	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> <tr> <td>Use</td> <td>required</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 80	Use	required										
Type	restriction (xsd:string)																
Length	1 .. 80																
Use	required																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>currencyCode</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>A code representing the currency of a particular</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	currencyCode	Status	1..1	Beschr. EDI	A code representing the currency of a particular								
Fachgruppe BiG																	
Name FG BiG	currencyCode																
Status	1..1																
Beschr. EDI	A code representing the currency of a particular																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td></td> <td>country or group of countries. ISO 4217 Code List</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Währung</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bd:Amount.currencyCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:CurrencyCode</td> </tr> <tr> <td>Beispiel</td> <td>CHF</td> </tr> </tbody> </table>	Fachgruppe BiG			country or group of countries. ISO 4217 Code List	Beschr. FG BiG	Währung	GDD URI	urn:gs1:gdd:bd:Amount.currencyCode	Codeliste	urn:gs1:gdd:cl:CurrencyCode	Beispiel	CHF				
Fachgruppe BiG																	
	country or group of countries. ISO 4217 Code List																
Beschr. FG BiG	Währung																
GDD URI	urn:gs1:gdd:bd:Amount.currencyCode																
Codeliste	urn:gs1:gdd:cl:CurrencyCode																
Beispiel	CHF																
<i>codeListVersion</i>	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 35												
Type	restriction (xsd:string)																
Length	1 .. 35																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>codeListVersion</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>CodeListenversion ISO-Währungen</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:cl:CurrencyCode</td> </tr> <tr> <td>Beispiel</td> <td>1</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	codeListVersion	Beschr. FG BiG	CodeListenversion ISO-Währungen	GDD URI	urn:gs1:gdd:cl:CurrencyCode	Beispiel	1		
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	codeListVersion																
Beschr. FG BiG	CodeListenversion ISO-Währungen																
GDD URI	urn:gs1:gdd:cl:CurrencyCode																
Beispiel	1																
transactionalTradeltem	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:TransactionalTradeltemType</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	ecom_common:TransactionalTradeltemType												
Occurrence	1 .. 1																
Type	ecom_common:TransactionalTradeltemType																
<i>xsd:sequence</i>																	
gtin	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:GTINType</td> </tr> <tr> <td>Pattern</td> <td>ld{14}</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	shared_common:GTINType	Pattern	ld{14}										
Occurrence	1 .. 1																
Type	shared_common:GTINType																
Pattern	ld{14}																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gtin</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Trade Item Number (GTIN), the GS1 key used for the identification of trade items.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Global Trade Item Number; Produkte ohne GTIN mit einer GTIN mit Präfix 20 auszeichnen</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:TradeltemIdentification.gtin</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>07612345000121</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gtin	Status	1..1	Beschr. EDI	Global Trade Item Number (GTIN), the GS1 key used for the identification of trade items.	Beschr. FG BiG	Global Trade Item Number; Produkte ohne GTIN mit einer GTIN mit Präfix 20 auszeichnen	GDD URI	urn:gs1:gdd:bie:TradeltemIdentification.gtin	Codeliste	-	Beispiel	07612345000121
Fachgruppe BiG																	
Name FG BiG	gtin																
Status	1..1																
Beschr. EDI	Global Trade Item Number (GTIN), the GS1 key used for the identification of trade items.																
Beschr. FG BiG	Global Trade Item Number; Produkte ohne GTIN mit einer GTIN mit Präfix 20 auszeichnen																
GDD URI	urn:gs1:gdd:bie:TradeltemIdentification.gtin																
Codeliste	-																
Beispiel	07612345000121																
additionalTradeltemIdentification	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. unbounded</td> </tr> <tr> <td>Type</td> <td>shared_common:AdditionalTradeltemIdentificationType</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> </tbody> </table>	Occurrence	0 .. unbounded	Type	shared_common:AdditionalTradeltemIdentificationType	Length	1 .. 80										
Occurrence	0 .. unbounded																
Type	shared_common:AdditionalTradeltemIdentificationType																
Length	1 .. 80																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>additionalTradeltemIdentification</td> </tr> <tr> <td>Status</td> <td>0..ounbounded</td> </tr> <tr> <td>Beschr. EDI</td> <td>Additional Trade Item Identification Data type</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zusätzliche Artikelidentifikation</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bd:AdditionalTradeltemIdentification</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>LIC1PROD1</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	additionalTradeltemIdentification	Status	0..ounbounded	Beschr. EDI	Additional Trade Item Identification Data type	Beschr. FG BiG	Zusätzliche Artikelidentifikation	GDD URI	urn:gs1:gdd:bd:AdditionalTradeltemIdentification	Codeliste	-	Beispiel	LIC1PROD1
Fachgruppe BiG																	
Name FG BiG	additionalTradeltemIdentification																
Status	0..ounbounded																
Beschr. EDI	Additional Trade Item Identification Data type																
Beschr. FG BiG	Zusätzliche Artikelidentifikation																
GDD URI	urn:gs1:gdd:bd:AdditionalTradeltemIdentification																
Codeliste	-																
Beispiel	LIC1PROD1																
<i>additionalTradeltemIdentificationTypeCode</i>	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> <tr> <td>Use</td> <td>required</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 80	Use	required										
Type	restriction (xsd:string)																
Length	1 .. 80																
Use	required																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>additionalTradeltemIdentificationTypeCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying an additional trade item identification type. Allowed code values are specified</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	additionalTradeltemIdentificationTypeCode	Status	0..1	Beschr. EDI	Code specifying an additional trade item identification type. Allowed code values are specified								
Fachgruppe BiG																	
Name FG BiG	additionalTradeltemIdentificationTypeCode																
Status	0..1																
Beschr. EDI	Code specifying an additional trade item identification type. Allowed code values are specified																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td></td> <td>in GS1 Code List AdditionalTradeItemIdentificationTypeCode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:AdditionalTradeItemIdentificationTypeCode&release=2</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zusätzliche Artikelidentifikation, z.B. HIBC, Artikelbeschreibung etc.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:AdditionalTradeItemIdentificationTypeCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:AdditionalTradeItemIdentificationTypeCode</td> </tr> <tr> <td>Beispiel</td> <td>HIBC</td> </tr> </tbody> </table>	Fachgruppe BiG			in GS1 Code List AdditionalTradeItemIdentificationTypeCode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:AdditionalTradeItemIdentificationTypeCode&release=2	Beschr. FG BiG	Zusätzliche Artikelidentifikation, z.B. HIBC, Artikelbeschreibung etc.	GDD URI	urn:gs1:gdd:bdt:AdditionalTradeItemIdentificationTypeCode	Codeliste	urn:gs1:gdd:cl:AdditionalTradeItemIdentificationTypeCode	Beispiel	HIBC				
Fachgruppe BiG																	
	in GS1 Code List AdditionalTradeItemIdentificationTypeCode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:AdditionalTradeItemIdentificationTypeCode&release=2																
Beschr. FG BiG	Zusätzliche Artikelidentifikation, z.B. HIBC, Artikelbeschreibung etc.																
GDD URI	urn:gs1:gdd:bdt:AdditionalTradeItemIdentificationTypeCode																
Codeliste	urn:gs1:gdd:cl:AdditionalTradeItemIdentificationTypeCode																
Beispiel	HIBC																
codeListVersion	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 35												
Type	restriction (xsd:string)																
Length	1 .. 35																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The snapshot of the code list at a certain point in time</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Version der Codeliste</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:AdditionalTradeItemIdentification.codeListVersion</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	The snapshot of the code list at a certain point in time	Beschr. FG BiG	Version der Codeliste	GDD URI	urn:gs1:gdd:bdt:AdditionalTradeItemIdentification.codeListVersion	Codeliste	-	Beispiel	2
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	The snapshot of the code list at a certain point in time																
Beschr. FG BiG	Version der Codeliste																
GDD URI	urn:gs1:gdd:bdt:AdditionalTradeItemIdentification.codeListVersion																
Codeliste	-																
Beispiel	2																
xsd:sequence tradeItemDescription	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:Description200Type</td> </tr> <tr> <td>Length</td> <td>1 .. 200</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Occurrence	0 .. 1	Type	shared_common:Description200Type	Length	1 .. 200								
Occurrence	1 .. 1																
Occurrence	0 .. 1																
Type	shared_common:Description200Type																
Length	1 .. 200																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>tradeItemDescription</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Textual description of the trade item.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Artikelbeschreibung</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:TransactionalTradeItem.tradeItemDescription</td> </tr> <tr> <td>Beispiel</td> <td>Skalpellgriff No. 3</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	tradeItemDescription	Status	0..1	Beschr. EDI	Textual description of the trade item.	Beschr. FG BiG	Artikelbeschreibung	GDD URI	urn:gs1:gdd:bie:TransactionalTradeItem.tradeItemDescription	Beispiel	Skalpellgriff No. 3		
Fachgruppe BiG																	
Name FG BiG	tradeItemDescription																
Status	0..1																
Beschr. EDI	Textual description of the trade item.																
Beschr. FG BiG	Artikelbeschreibung																
GDD URI	urn:gs1:gdd:bie:TransactionalTradeItem.tradeItemDescription																
Beispiel	Skalpellgriff No. 3																
languageCode	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> <tr> <td>Use</td> <td>required</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 80	Use	required										
Type	restriction (xsd:string)																
Length	1 .. 80																
Use	required																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>languageCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:LanguageCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:LanguageCode</td> </tr> <tr> <td>Beispiel</td> <td>DE</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	languageCode	Status	0..1	Beschr. EDI	Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode	Beschr. FG BiG	Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1	GDD URI	urn:gs1:gdd:bdt:LanguageCode	Codeliste	urn:gs1:gdd:cl:LanguageCode	Beispiel	DE
Fachgruppe BiG																	
Name FG BiG	languageCode																
Status	0..1																
Beschr. EDI	Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode																
Beschr. FG BiG	Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1																
GDD URI	urn:gs1:gdd:bdt:LanguageCode																
Codeliste	urn:gs1:gdd:cl:LanguageCode																
Beispiel	DE																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																
<i>codeListVersion</i>	<p>Type restriction (xsd:string) Length 1 .. 35</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>codeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The snapshot of the code list at a certain point in time.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Code Listen Version</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:cl:LanguageCode</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2002</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	codeListVersion	Status	0..1	Beschr. EDI	The snapshot of the code list at a certain point in time.	Beschr. FG BiG	Code Listen Version	GDD URI	urn:gs1:gdd:cl:LanguageCode	Codeliste	-	Beispiel	2002
Fachgruppe BiG																	
Name FG BiG	codeListVersion																
Status	0..1																
Beschr. EDI	The snapshot of the code list at a certain point in time.																
Beschr. FG BiG	Code Listen Version																
GDD URI	urn:gs1:gdd:cl:LanguageCode																
Codeliste	-																
Beispiel	2002																
transactionalItemData	<p>Occurrence 0 .. unbounded Type ecom_common:TransactionalItemType</p>																
<i>xsd:sequence</i>	<p>Occurrence 1 .. 1</p>																
batchNumber	<p>Occurrence 0 .. 1 Type restriction (xsd:string) Length 1 .. 80</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>batchNumber</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>A batch unites products or items that have undergone or are grouped together to undergo the same transformation process, not necessarily a production process.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Lot-/Batch- Nummer des zu liefernden Artikels.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:TransactionalItemData.lotNumber</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>5-889</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	batchNumber	Status	0..1	Beschr. EDI	A batch unites products or items that have undergone or are grouped together to undergo the same transformation process, not necessarily a production process.	Beschr. FG BiG	Lot-/Batch- Nummer des zu liefernden Artikels.	GDD URI	urn:gs1:gdd:bie:TransactionalItemData.lotNumber	Codeliste	-	Beispiel	5-889
Fachgruppe BiG																	
Name FG BiG	batchNumber																
Status	0..1																
Beschr. EDI	A batch unites products or items that have undergone or are grouped together to undergo the same transformation process, not necessarily a production process.																
Beschr. FG BiG	Lot-/Batch- Nummer des zu liefernden Artikels.																
GDD URI	urn:gs1:gdd:bie:TransactionalItemData.lotNumber																
Codeliste	-																
Beispiel	5-889																
itemExpirationDate	<p>Occurrence 0 .. 1 Type xsd:date</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>itemExpirationDate</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The date after which the product should not be used or consumed. Its meaning is determined based on the trade item context (e.g., for food, the date will indicate the possibility of a direct health risk resulting from use of the product after the date, for pharmaceutical products, it will indicate the possibility of an indirect health risk resulting from the ineffectiveness of the product after the date). It is often referred to as "use by date" or "maximum durability date."</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Varfalldatum</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:TransactionalItemData.itemExpirationDate</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2016-07-31</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	itemExpirationDate	Status	0..1	Beschr. EDI	The date after which the product should not be used or consumed. Its meaning is determined based on the trade item context (e.g., for food, the date will indicate the possibility of a direct health risk resulting from use of the product after the date, for pharmaceutical products, it will indicate the possibility of an indirect health risk resulting from the ineffectiveness of the product after the date). It is often referred to as "use by date" or "maximum durability date."	Beschr. FG BiG	Varfalldatum	GDD URI	urn:gs1:gdd:bie:TransactionalItemData.itemExpirationDate	Codeliste	-	Beispiel	2016-07-31
Fachgruppe BiG																	
Name FG BiG	itemExpirationDate																
Status	0..1																
Beschr. EDI	The date after which the product should not be used or consumed. Its meaning is determined based on the trade item context (e.g., for food, the date will indicate the possibility of a direct health risk resulting from use of the product after the date, for pharmaceutical products, it will indicate the possibility of an indirect health risk resulting from the ineffectiveness of the product after the date). It is often referred to as "use by date" or "maximum durability date."																
Beschr. FG BiG	Varfalldatum																
GDD URI	urn:gs1:gdd:bie:TransactionalItemData.itemExpirationDate																
Codeliste	-																
Beispiel	2016-07-31																
serialNumber	<p>Occurrence 0 .. unbounded Type restriction (xsd:string) Length 1 .. 20</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>serialNumber</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	serialNumber												
Fachgruppe BiG																	
Name FG BiG	serialNumber																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation
-------------------	------------

Fachgruppe BiG	
Status	0..unbounded
Beschr. EDI	A unique identifier assigned to a specific trade item.
Beschr. FG BiG	Seriennummer
GDD URI	urn:gs1:gdd:bie:TransactionalItemData.serialNumber
Codeliste	-
Beispiel	89-22345

serialNumberRange	Occurrence 0 .. unbounded
xsd:sequence	Type shared_common:StringRangeType
maximumValue	Occurrence 1 .. 1
	Occurrence 0 .. 1
	Type xsd:string

Fachgruppe BiG	
Name FG BiG	maximumValue
Status	0..1
Beschr. EDI	The minimum and maximum value of one or more ranges of serial numbers related to the specified items.
Beschr. FG BiG	Höchster Wert Seriennummer
GDD URI	urn:gs1:gdd:bie:TransactionalItemData.serialNumberRange.StringRange
Codeliste	-
Beispiel	89-22345

minimumValue	Occurrence 0 .. 1
	Type xsd:string

Fachgruppe BiG	
Name FG BiG	minimumValue
Status	0..1
Beschr. EDI	Specifies the lower limit of the string range.
Beschr. FG BiG	Tiefster Wert Seriennummer
GDD URI	urn:gs1:gdd:bie:TransactionalItemData.serialNumberRange.StringRange
Codeliste	-
Beispiel	89-22335

colour	Occurrence 0 .. unbounded
xsd:sequence	Type shared_common:ColourType
colourCode	Occurrence 1 .. 1
	Occurrence 0 .. 1
	Type shared_common:ColourCodeType
	Length 1 .. 80

Fachgruppe BiG	
Name FG BiG	colourCode
Status	0..1
Beschr. EDI	Information specifying a colour in text and / or coded format. Codeliste: urn:gs1:gdd:cl:ColourCodeListCode
Beschr. FG BiG	Farbcode
GDD URI	urn:gs1:gdd:bie:Colour
Codeliste	-
Beispiel	116C

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
colourCodeListCode	<p>Type restriction (xsd:string) Length 1 .. 80 Use required</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>colourCodeListCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying a colour code list. Allowed code values are specified in GS1 Code List ColourCodeListCode.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Codeliste Farben</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:ColourCode.colourCodeListCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:ColourCodeListCode</td> </tr> <tr> <td>Beispiel</td> <td>3</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	colourCodeListCode	Status	0..1	Beschr. EDI	Code specifying a colour code list. Allowed code values are specified in GS1 Code List ColourCodeListCode.	Beschr. FG BiG	Codeliste Farben	GDD URI	urn:gs1:gdd:bdt:ColourCode.colourCodeListCode	Codeliste	urn:gs1:gdd:cl:ColourCodeListCode	Beispiel	3
Fachgruppe BiG																	
Name FG BiG	colourCodeListCode																
Status	0..1																
Beschr. EDI	Code specifying a colour code list. Allowed code values are specified in GS1 Code List ColourCodeListCode.																
Beschr. FG BiG	Codeliste Farben																
GDD URI	urn:gs1:gdd:bdt:ColourCode.colourCodeListCode																
Codeliste	urn:gs1:gdd:cl:ColourCodeListCode																
Beispiel	3																
<i>colourCodeListVersion</i>	<p>Type restriction (xsd:string) Length 1 .. 35</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>colourCodeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The version of the ColourCodeListCode code list.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Code List Version</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:ColourCode.colourCodeListVersion</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>3</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	colourCodeListVersion	Status	0..1	Beschr. EDI	The version of the ColourCodeListCode code list.	Beschr. FG BiG	Code List Version	GDD URI	urn:gs1:gdd:bdt:ColourCode.colourCodeListVersion	Codeliste	-	Beispiel	3
Fachgruppe BiG																	
Name FG BiG	colourCodeListVersion																
Status	0..1																
Beschr. EDI	The version of the ColourCodeListCode code list.																
Beschr. FG BiG	Code List Version																
GDD URI	urn:gs1:gdd:bdt:ColourCode.colourCodeListVersion																
Codeliste	-																
Beispiel	3																
colourDescription	<p>Occurrence 0 .. unbounded Type shared_common:Description80Type Length 1 .. 80</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>colourDescription</td> </tr> <tr> <td>Status</td> <td>0..unbounded</td> </tr> <tr> <td>Beschr. EDI</td> <td>A description of a colour of an object.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>blau</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:Colour.colourDescription</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>blau</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	colourDescription	Status	0..unbounded	Beschr. EDI	A description of a colour of an object.	Beschr. FG BiG	blau	GDD URI	urn:gs1:gdd:bie:Colour.colourDescription	Codeliste	-	Beispiel	blau
Fachgruppe BiG																	
Name FG BiG	colourDescription																
Status	0..unbounded																
Beschr. EDI	A description of a colour of an object.																
Beschr. FG BiG	blau																
GDD URI	urn:gs1:gdd:bie:Colour.colourDescription																
Codeliste	-																
Beispiel	blau																
<i>languageCode</i>	<p>Type restriction (xsd:string) Length 1 .. 80 Use required</p> <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>languageCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:LanguageCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:LanguageCode</td> </tr> <tr> <td>Beispiel</td> <td>DE</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	languageCode	Status	0..1	Beschr. EDI	Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode	Beschr. FG BiG	Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1	GDD URI	urn:gs1:gdd:bdt:LanguageCode	Codeliste	urn:gs1:gdd:cl:LanguageCode	Beispiel	DE
Fachgruppe BiG																	
Name FG BiG	languageCode																
Status	0..1																
Beschr. EDI	Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode																
Beschr. FG BiG	Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1																
GDD URI	urn:gs1:gdd:bdt:LanguageCode																
Codeliste	urn:gs1:gdd:cl:LanguageCode																
Beispiel	DE																
<i>codeListVersion</i>	<p>Type restriction (xsd:string) Length 1 .. 35</p>																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																						
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>CodeListeVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The snapshot of the code list at a certain point in time.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>CodeListe</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:LanguageCode</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>3</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	CodeListeVersion	Status	0..1	Beschr. EDI	The snapshot of the code list at a certain point in time.	Beschr. FG BiG	CodeListe	GDD URI	urn:gs1:gdd:bdt:LanguageCode	Codeliste	-	Beispiel	3						
Fachgruppe BiG																							
Name FG BiG	CodeListeVersion																						
Status	0..1																						
Beschr. EDI	The snapshot of the code list at a certain point in time.																						
Beschr. FG BiG	CodeListe																						
GDD URI	urn:gs1:gdd:bdt:LanguageCode																						
Codeliste	-																						
Beispiel	3																						
size	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. unbounded</td> </tr> <tr> <td>Type</td> <td>shared_common:SizeType</td> </tr> </tbody> </table>	Occurrence	0 .. unbounded	Type	shared_common:SizeType																		
Occurrence	0 .. unbounded																						
Type	shared_common:SizeType																						
xsd:sequence descriptiveSize	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>size</td> </tr> <tr> <td>Status</td> <td>0 .. unbounded</td> </tr> <tr> <td>Beschr. EDI</td> <td>The physical dimensions or proportions of the transactional trade item depicted as a code or a description.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Grösse</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:TransactionalTradeItem..Size</td> </tr> <tr> <td>Beispiel</td> <td>42</td> </tr> </tbody> </table> <table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:Description80Type</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	size	Status	0 .. unbounded	Beschr. EDI	The physical dimensions or proportions of the transactional trade item depicted as a code or a description.	Beschr. FG BiG	Grösse	GDD URI	urn:gs1:gdd:bie:TransactionalTradeItem..Size	Beispiel	42	Occurrence	1 .. 1	Occurrence	0 .. 1	Type	shared_common:Description80Type	Length	1 .. 80
Fachgruppe BiG																							
Name FG BiG	size																						
Status	0 .. unbounded																						
Beschr. EDI	The physical dimensions or proportions of the transactional trade item depicted as a code or a description.																						
Beschr. FG BiG	Grösse																						
GDD URI	urn:gs1:gdd:bie:TransactionalTradeItem..Size																						
Beispiel	42																						
Occurrence	1 .. 1																						
Occurrence	0 .. 1																						
Type	shared_common:Description80Type																						
Length	1 .. 80																						
languageCode	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>descriptiveSize</td> </tr> <tr> <td>Status</td> <td>0..unbounded</td> </tr> <tr> <td>Beschr. EDI</td> <td>A description of the size of an object.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Grösse</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:Size.descriptiveSize</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>20 x 30 x 50 cm</td> </tr> </tbody> </table> <table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 80</td> </tr> <tr> <td>Use</td> <td>required</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	descriptiveSize	Status	0..unbounded	Beschr. EDI	A description of the size of an object.	Beschr. FG BiG	Grösse	GDD URI	urn:gs1:gdd:bie:Size.descriptiveSize	Codeliste	-	Beispiel	20 x 30 x 50 cm	Type	restriction (xsd:string)	Length	1 .. 80	Use	required
Fachgruppe BiG																							
Name FG BiG	descriptiveSize																						
Status	0..unbounded																						
Beschr. EDI	A description of the size of an object.																						
Beschr. FG BiG	Grösse																						
GDD URI	urn:gs1:gdd:bie:Size.descriptiveSize																						
Codeliste	-																						
Beispiel	20 x 30 x 50 cm																						
Type	restriction (xsd:string)																						
Length	1 .. 80																						
Use	required																						
codeListVersion	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>languageCode</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:LanguageCode</td> </tr> <tr> <td>Codeliste</td> <td>urn:gs1:gdd:cl:LanguageCode</td> </tr> <tr> <td>Beispiel</td> <td>DE</td> </tr> </tbody> </table> <table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	languageCode	Status	0..1	Beschr. EDI	Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode	Beschr. FG BiG	Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1	GDD URI	urn:gs1:gdd:bdt:LanguageCode	Codeliste	urn:gs1:gdd:cl:LanguageCode	Beispiel	DE	Type	restriction (xsd:string)	Length	1 .. 35		
Fachgruppe BiG																							
Name FG BiG	languageCode																						
Status	0..1																						
Beschr. EDI	Code specifying a language. Allowed code values are specified in GS1 Code List LanguageCode																						
Beschr. FG BiG	Sprachcode. Codeliste: http://apps.gs1.org/GDD/Pages/clDetails.aspx?semanticURN=urn:gs1:gdd:cl:LanguageCode&release=1																						
GDD URI	urn:gs1:gdd:bdt:LanguageCode																						
Codeliste	urn:gs1:gdd:cl:LanguageCode																						
Beispiel	DE																						
Type	restriction (xsd:string)																						
Length	1 .. 35																						
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>CodeListeVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	CodeListeVersion	Status	0..1																
Fachgruppe BiG																							
Name FG BiG	CodeListeVersion																						
Status	0..1																						

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation
-------------------	------------

Fachgruppe BiG	
Beschr. EDI	The snapshot of the code list at a certain point in time.
Beschr. FG BiG	CodeListe
GDD URI	urn:gs1:gdd:bdt:LanguageCode
CodeListe	-
Beispiel	3

sizeCode	Occurrence 0 .. 1 Type shared_common:SizeCodeType Length 1 .. 80
-----------------	--

Fachgruppe BiG	
Name FG BiG	sizeCode
Status	0..1
Beschr. EDI	Code specifying the size of an object and the size coding system being applied, for example L (buyer assigned)
Beschr. FG BiG	Grösse
GDD URI	urn:gs1:gdd:bie:Size.sizeCode
CodeListe	-
Beispiel	42

sizeCodeListCode	Type restriction (xsd:string) Length 1 .. 80 Use required
-------------------------	---

Fachgruppe BiG	
Name FG BiG	sizeCodeListCode
Status	0..1
Beschr. EDI	Code specifying a size code list. Allowed code values are specified in GS1 Code List SizeCodeListCode.
Beschr. FG BiG	Grössenangabe. CodeListe: urn:gs1:gdd:cl:SizeCodeListCode
GDD URI	urn:gs1:gdd:bdt:SizeCode.sizeCodeListCode
CodeListe	-
Beispiel	-

sizeCodeListDescription	Type restriction (xsd:string) Length 1 .. 80
--------------------------------	---

Fachgruppe BiG	
Name FG BiG	sizeCodeListDescription
Status	0..1
Beschr. EDI	A description of the size code list used to populate the size code for example National Retail Federation – Standard Colour & Size Codes
Beschr. FG BiG	Beschreibung der Grössentabelle
GDD URI	urn:gs1:gdd:bdt:SizeCode.sizeCodeListDescription
CodeListe	-
Beispiel	Schuhgrößen Europa

codeListVersion	Type restriction (xsd:string) Length 1 .. 35
------------------------	---

Fachgruppe BiG	
Name FG BiG	codeListVersion
Status	0..1

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																		
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Beschr. EDI</td> <td>The version of the applied size code list.</td> </tr> <tr> <td>Beschr. FG</td> <td>Version der Codeliste</td> </tr> <tr> <td>BiG</td> <td></td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:SizeCode_codeListVersion</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>-</td> </tr> </tbody> </table>	Fachgruppe BiG		Beschr. EDI	The version of the applied size code list.	Beschr. FG	Version der Codeliste	BiG		GDD URI	urn:gs1:gdd:bdt:SizeCode_codeListVersion	Codeliste	-	Beispiel	-				
Fachgruppe BiG																			
Beschr. EDI	The version of the applied size code list.																		
Beschr. FG	Version der Codeliste																		
BiG																			
GDD URI	urn:gs1:gdd:bdt:SizeCode_codeListVersion																		
Codeliste	-																		
Beispiel	-																		
sizeCodeListVersion	<table border="1"> <tbody> <tr> <td>Type</td> <td>restriction (xsd:string)</td> </tr> <tr> <td>Length</td> <td>1 .. 35</td> </tr> </tbody> </table>	Type	restriction (xsd:string)	Length	1 .. 35														
Type	restriction (xsd:string)																		
Length	1 .. 35																		
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>sizeCodeListVersion</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The version of the SizeCodeListCode code list.</td> </tr> <tr> <td>Beschr. FG</td> <td>Version der Grösstentabelle</td> </tr> <tr> <td>BiG</td> <td></td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bdt:SizeCode.sizeCodeListVersion</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>-</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	sizeCodeListVersion	Status	0..1	Beschr. EDI	The version of the SizeCodeListCode code list.	Beschr. FG	Version der Grösstentabelle	BiG		GDD URI	urn:gs1:gdd:bdt:SizeCode.sizeCodeListVersion	Codeliste	-	Beispiel	-
Fachgruppe BiG																			
Name FG BiG	sizeCodeListVersion																		
Status	0..1																		
Beschr. EDI	The version of the SizeCodeListCode code list.																		
Beschr. FG	Version der Grösstentabelle																		
BiG																			
GDD URI	urn:gs1:gdd:bdt:SizeCode.sizeCodeListVersion																		
Codeliste	-																		
Beispiel	-																		
backOrderInformation	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>order_response:OrderResponseLineItemDetailType</td> </tr> </tbody> </table>	Occurrence	0 .. 1	Type	order_response:OrderResponseLineItemDetailType														
Occurrence	0 .. 1																		
Type	order_response:OrderResponseLineItemDetailType																		
xsd:sequence																			
confirmedQuantity	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:QuantityType</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	shared_common:QuantityType														
Occurrence	1 .. 1																		
Type	shared_common:QuantityType																		
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>confirmedQuantity</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The quantity which has been confirmed by the seller.</td> </tr> <tr> <td>Beschr. FG</td> <td>Bestätigte Liefermenge</td> </tr> <tr> <td>BiG</td> <td></td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>24</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	confirmedQuantity	Status	1..1	Beschr. EDI	The quantity which has been confirmed by the seller.	Beschr. FG	Bestätigte Liefermenge	BiG		GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity	Codeliste	-	Beispiel	24
Fachgruppe BiG																			
Name FG BiG	confirmedQuantity																		
Status	1..1																		
Beschr. EDI	The quantity which has been confirmed by the seller.																		
Beschr. FG	Bestätigte Liefermenge																		
BiG																			
GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity																		
Codeliste	-																		
Beispiel	24																		
orderLogisticalInformation	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:OrderLogisticalInformationType</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	ecom_common:OrderLogisticalInformationType														
Occurrence	1 .. 1																		
Type	ecom_common:OrderLogisticalInformationType																		
xsd:sequence																			
inventoryLocation	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:TransactionalPartyType</td> </tr> </tbody> </table>	Occurrence	0 .. 1	Type	ecom_common:TransactionalPartyType														
Occurrence	0 .. 1																		
Type	ecom_common:TransactionalPartyType																		
xsd:sequence																			
gln	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> <tr> <td>Type</td> <td>shared_common:GLNType</td> </tr> <tr> <td>Pattern</td> <td>\d{13}</td> </tr> </tbody> </table>	Occurrence	1 .. 1	Type	shared_common:GLNType	Pattern	\d{13}												
Occurrence	1 .. 1																		
Type	shared_common:GLNType																		
Pattern	\d{13}																		
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG</td> <td>GLN des Lagerortes</td> </tr> <tr> <td>BiG</td> <td></td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification.gln</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.	Beschr. FG	GLN des Lagerortes	BiG		GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln	Codeliste	-	Beispiel	7612345670010
Fachgruppe BiG																			
Name FG BiG	gln																		
Status	0..1																		
Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.																		
Beschr. FG	GLN des Lagerortes																		
BiG																			
GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln																		
Codeliste	-																		
Beispiel	7612345670010																		
ultimateConsignee	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>0 .. 1</td> </tr> <tr> <td>Type</td> <td>ecom_common:TransactionalPartyType</td> </tr> </tbody> </table>	Occurrence	0 .. 1	Type	ecom_common:TransactionalPartyType														
Occurrence	0 .. 1																		
Type	ecom_common:TransactionalPartyType																		
xsd:sequence																			
	<table border="1"> <tbody> <tr> <td>Occurrence</td> <td>1 .. 1</td> </tr> </tbody> </table>	Occurrence	1 .. 1																
Occurrence	1 .. 1																		

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
gln	Occurrence 0 .. 1 Type shared_common:GLNType Pattern \d{13}																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>gln</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Global Location Number (GLN), the GS1 key used for the identification of parties and locations.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>GLN des Endempfängers.</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:PartyIdentification.gln</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>7612345670010</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	gln	Status	0..1	Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.	Beschr. FG BiG	GLN des Endempfängers.	GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln	Codeliste	-	Beispiel	7612345670010
Fachgruppe BiG																	
Name FG BiG	gln																
Status	0..1																
Beschr. EDI	Global Location Number (GLN), the GS1 key used for the identification of parties and locations.																
Beschr. FG BiG	GLN des Endempfängers.																
GDD URI	urn:gs1:gdd:bie:PartyIdentification.gln																
Codeliste	-																
Beispiel	7612345670010																
orderLogisticalDateInformation	Occurrence 0 .. 1 Type ecom_common:OrderLogisticalDateInformationType																
<i>xsd:sequence</i>																	
requestedDeliveryDateRange	Occurrence 1 .. 1 Type shared_common:DateTimeRangeType																
<i>xsd:sequence</i>																	
beginDate	Occurrence 1 .. 1 Type xsd:date																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>beginDate</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Date specifying the first day for the date time range.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeitfenster für Lieferung, Startdatum</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateTimeRange.beginDate</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2014-07-31</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	beginDate	Status	0..1	Beschr. EDI	Date specifying the first day for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Startdatum	GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginDate	Codeliste	-	Beispiel	2014-07-31
Fachgruppe BiG																	
Name FG BiG	beginDate																
Status	0..1																
Beschr. EDI	Date specifying the first day for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Startdatum																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginDate																
Codeliste	-																
Beispiel	2014-07-31																
beginTime	Occurrence 0 .. 1 Type xsd:time																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>beginTime</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Time specifying the start time for the date time range.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeitfenster für Lieferung, Startzeit</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateTimeRange.beginTime</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>08:00</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	beginTime	Status	0..1	Beschr. EDI	Time specifying the start time for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Startzeit	GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginTime	Codeliste	-	Beispiel	08:00
Fachgruppe BiG																	
Name FG BiG	beginTime																
Status	0..1																
Beschr. EDI	Time specifying the start time for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Startzeit																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginTime																
Codeliste	-																
Beispiel	08:00																
endDate	Occurrence 0 .. 1 Type xsd:date																
	<table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>endDate</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Date specifying the last day for the date time range.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeitfenster für Lieferung, Enddatum</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateTimeRange.endDate</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2014-08.05</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	endDate	Status	0..1	Beschr. EDI	Date specifying the last day for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Enddatum	GDD URI	urn:gs1:gdd:bie:DateTimeRange.endDate	Codeliste	-	Beispiel	2014-08.05
Fachgruppe BiG																	
Name FG BiG	endDate																
Status	0..1																
Beschr. EDI	Date specifying the last day for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Enddatum																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.endDate																
Codeliste	-																
Beispiel	2014-08.05																

Bold = Element, *Italic* = Attribute, Grey = Group

Element/Attribute	Annotation																
endTime	Occurrence 0 .. 1 Type xsd:time <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>endTime</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>Time specifying the end time for the date time range.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Zeitfenster für Lieferung, Endzeit</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateTimeRange.endTime</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>17:00</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	endTime	Status	0..1	Beschr. EDI	Time specifying the end time for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Endzeit	GDD URI	urn:gs1:gdd:bie:DateTimeRange.endTime	Codeliste	-	Beispiel	17:00
Fachgruppe BiG																	
Name FG BiG	endTime																
Status	0..1																
Beschr. EDI	Time specifying the end time for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Endzeit																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.endTime																
Codeliste	-																
Beispiel	17:00																
requestedDeliveryDateTime	Occurrence 0 .. 1 Type shared_common:DateOptionalTimeType Occurrence 1 .. 1 Occurrence 1 .. 1 Type xsd:date <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>date</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The specification of a day as calendar date.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Lieferdatum</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateOptionalTime.date</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2014-07-31</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	date	Status	1..1	Beschr. EDI	The specification of a day as calendar date.	Beschr. FG BiG	Lieferdatum	GDD URI	urn:gs1:gdd:bie:DateOptionalTime.date	Codeliste	-	Beispiel	2014-07-31
Fachgruppe BiG																	
Name FG BiG	date																
Status	1..1																
Beschr. EDI	The specification of a day as calendar date.																
Beschr. FG BiG	Lieferdatum																
GDD URI	urn:gs1:gdd:bie:DateOptionalTime.date																
Codeliste	-																
Beispiel	2014-07-31																
time	Occurrence 0 .. 1 Type xsd:time <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>time</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The specification of a point in time during the day.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Lieferzeit</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateOptionalTime.time</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>14:00</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	time	Status	0..1	Beschr. EDI	The specification of a point in time during the day.	Beschr. FG BiG	Lieferzeit	GDD URI	urn:gs1:gdd:bie:DateOptionalTime.time	Codeliste	-	Beispiel	14:00
Fachgruppe BiG																	
Name FG BiG	time																
Status	0..1																
Beschr. EDI	The specification of a point in time during the day.																
Beschr. FG BiG	Lieferzeit																
GDD URI	urn:gs1:gdd:bie:DateOptionalTime.time																
Codeliste	-																
Beispiel	14:00																
orderResponseLineItemDetail	Occurrence 0 .. unbounded Type order_response:OrderResponseLineItemDetailType Occurrence 1 .. 1 Occurrence 1 .. 1 Type shared_common:QuantityType <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>confirmedQuantity</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The quantity which has been confirmed by the seller.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Bestätigte Liefermenge</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>24</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	confirmedQuantity	Status	1..1	Beschr. EDI	The quantity which has been confirmed by the seller.	Beschr. FG BiG	Bestätigte Liefermenge	GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity	Codeliste	-	Beispiel	24
Fachgruppe BiG																	
Name FG BiG	confirmedQuantity																
Status	1..1																
Beschr. EDI	The quantity which has been confirmed by the seller.																
Beschr. FG BiG	Bestätigte Liefermenge																
GDD URI	urn:gs1:gdd:bie:OrderResponseLineItem.confirmedQuantity																
Codeliste	-																
Beispiel	24																
orderLogisticalInformation	Occurrence 1 .. 1 Type ecom_common:OrderLogisticalInformationType Occurrence 1 .. 1																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
orderLogisticalDateInformation	Occurrence 0 .. 1 Type ecom_common:OrderLogisticalDateInformationType																
xsd:sequence																	
requestedDeliveryDateRange	Occurrence 0 .. 1 Type shared_common:DateTimeRangeType																
xsd:sequence																	
beginDate	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xsd:date																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>beginDate</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Date specifying the first day for the date time range.</td></tr> <tr><td>Beschr. FG BiG</td><td>Zeitfenster für Lieferung, Startdatum</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.beginDate</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>2014-07-31</td></tr> </table>	Fachgruppe BiG		Name FG BiG	beginDate	Status	0..1	Beschr. EDI	Date specifying the first day for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Startdatum	GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginDate	Codeliste	-	Beispiel	2014-07-31
Fachgruppe BiG																	
Name FG BiG	beginDate																
Status	0..1																
Beschr. EDI	Date specifying the first day for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Startdatum																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginDate																
Codeliste	-																
Beispiel	2014-07-31																
beginTime	Occurrence 0 .. 1 Type xsd:time																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>beginTime</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Time specifying the start time for the date time range.</td></tr> <tr><td>Beschr. FG BiG</td><td>Zeitfenster für Lieferung, Startzeit</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.beginTime</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>08:00</td></tr> </table>	Fachgruppe BiG		Name FG BiG	beginTime	Status	0..1	Beschr. EDI	Time specifying the start time for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Startzeit	GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginTime	Codeliste	-	Beispiel	08:00
Fachgruppe BiG																	
Name FG BiG	beginTime																
Status	0..1																
Beschr. EDI	Time specifying the start time for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Startzeit																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.beginTime																
Codeliste	-																
Beispiel	08:00																
endDate	Occurrence 0 .. 1 Type xsd:date																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>endDate</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Date specifying the last day for the date time range.</td></tr> <tr><td>Beschr. FG BiG</td><td>Zeitfenster für Lieferung, Enddatum</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.endDate</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>2014-08-05</td></tr> </table>	Fachgruppe BiG		Name FG BiG	endDate	Status	0..1	Beschr. EDI	Date specifying the last day for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Enddatum	GDD URI	urn:gs1:gdd:bie:DateTimeRange.endDate	Codeliste	-	Beispiel	2014-08-05
Fachgruppe BiG																	
Name FG BiG	endDate																
Status	0..1																
Beschr. EDI	Date specifying the last day for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Enddatum																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.endDate																
Codeliste	-																
Beispiel	2014-08-05																
endTime	Occurrence 0 .. 1 Type xsd:time																
	<table border="1"> <tr><td colspan="2">Fachgruppe BiG</td></tr> <tr><td>Name FG BiG</td><td>endTime</td></tr> <tr><td>Status</td><td>0..1</td></tr> <tr><td>Beschr. EDI</td><td>Time specifying the end time for the date time range.</td></tr> <tr><td>Beschr. FG BiG</td><td>Zeitfenster für Lieferung, Endzeit</td></tr> <tr><td>GDD URI</td><td>urn:gs1:gdd:bie:DateTimeRange.endTime</td></tr> <tr><td>Codeliste</td><td>-</td></tr> <tr><td>Beispiel</td><td>17:00</td></tr> </table>	Fachgruppe BiG		Name FG BiG	endTime	Status	0..1	Beschr. EDI	Time specifying the end time for the date time range.	Beschr. FG BiG	Zeitfenster für Lieferung, Endzeit	GDD URI	urn:gs1:gdd:bie:DateTimeRange.endTime	Codeliste	-	Beispiel	17:00
Fachgruppe BiG																	
Name FG BiG	endTime																
Status	0..1																
Beschr. EDI	Time specifying the end time for the date time range.																
Beschr. FG BiG	Zeitfenster für Lieferung, Endzeit																
GDD URI	urn:gs1:gdd:bie:DateTimeRange.endTime																
Codeliste	-																
Beispiel	17:00																
requestedDeliveryDateTime	Occurrence 0 .. 1 Type shared_common:DateOptionalTimeType																
xsd:sequence	Occurrence 1 .. 1																

Bold = Element, Italic = Attribute, Grey = Group

Element/Attribute	Annotation																
date	Occurrence 1 .. 1 Type xsd:date <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>date</td> </tr> <tr> <td>Status</td> <td>1..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The specification of a day as calendar date.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Lieferdatum</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateOptionalTime.date</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>2014-07-31</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	date	Status	1..1	Beschr. EDI	The specification of a day as calendar date.	Beschr. FG BiG	Lieferdatum	GDD URI	urn:gs1:gdd:bie:DateOptionalTime.date	Codeliste	-	Beispiel	2014-07-31
Fachgruppe BiG																	
Name FG BiG	date																
Status	1..1																
Beschr. EDI	The specification of a day as calendar date.																
Beschr. FG BiG	Lieferdatum																
GDD URI	urn:gs1:gdd:bie:DateOptionalTime.date																
Codeliste	-																
Beispiel	2014-07-31																
time	Occurrence 0 .. 1 Type xsd:time <table border="1"> <thead> <tr> <th colspan="2">Fachgruppe BiG</th> </tr> </thead> <tbody> <tr> <td>Name FG BiG</td> <td>time</td> </tr> <tr> <td>Status</td> <td>0..1</td> </tr> <tr> <td>Beschr. EDI</td> <td>The specification of a point in time during the day.</td> </tr> <tr> <td>Beschr. FG BiG</td> <td>Lieferzeit</td> </tr> <tr> <td>GDD URI</td> <td>urn:gs1:gdd:bie:DateOptionalTime.time</td> </tr> <tr> <td>Codeliste</td> <td>-</td> </tr> <tr> <td>Beispiel</td> <td>14:00</td> </tr> </tbody> </table>	Fachgruppe BiG		Name FG BiG	time	Status	0..1	Beschr. EDI	The specification of a point in time during the day.	Beschr. FG BiG	Lieferzeit	GDD URI	urn:gs1:gdd:bie:DateOptionalTime.time	Codeliste	-	Beispiel	14:00
Fachgruppe BiG																	
Name FG BiG	time																
Status	0..1																
Beschr. EDI	The specification of a point in time during the day.																
Beschr. FG BiG	Lieferzeit																
GDD URI	urn:gs1:gdd:bie:DateOptionalTime.time																
Codeliste	-																
Beispiel	14:00																

GS1 Schweiz – Zusammen Werte schaffen

GS1 Schweiz ist die Kompetenzplattform für nachhaltige Wertschöpfung auf der Basis optimierter Waren- und Informationsflüsse. Als Fachverband mit rund 5000 Mitgliedsunternehmen vernetzt GS1 Schweiz Beteiligte, fördert die Kollaboration und vermittelt Kompetenz in Wertschöpfungsnetzwerken. Globale GS1 Standards und Prozessmodelle ermöglichen die Gestaltung effizienter Wertschöpfungsketten.

GS1 Switzerland

Monbijoustrasse 68

CH - 3007 Bern

T +41 58 800 70 00

E info@gs1.ch

www.gs1.ch

